HOW TO APPLY CUTEK® WOOD REVIVER



A SIMPLE STEP-BY-STEP GUIDE

1 PROTECT AND TEST

Protect adjacent surfaces, vegetation, vehicles and pedestrian areas. Test a small section first to determine the required dilution, working time and amount of product.

2 USE UNDILUTED

CUTEK® Wood Reviver must be used at full strength. Do not dilute with water. Always test on a small area of your wood to check the results before treating the entire surface.

3 WET THE SURFACE

Thoroughly wet the wood with clean water. Apply Wood Reviver liberally using a brush, roller, broom or low-pressure garden sprayer.

4 APPLY AND ALLOW TO WORK

Leave Wood Reviver on wood for 1–4 hours, depending on severity of staining or discolouration. If needed, leave for up to 24 hours, though longer periods may make rinsing more difficult. Moderately scrub stubborn areas with a stiff fibre brush if required.

5 RINSE THOROUGHLY

Rinse thoroughly using a pressure washer at approximately 750 psi with a fan spray . Work from the highest point down, following the grain, until there is minimal or no sudsing.

PRO TIP
CUTEK® WOOD SOLUTIONS

A garden hose is not sufficient to remove CUTEK® Wood Reviver. Adjust the pressure or working distance to avoid damaging the wood fibers. Go along the grain, not across it and never use a turbo nozzle

- **DOES NOT STRIP OLD COATINGS:** **Remove existing coatings with CUTEK® Wood Stripper first.**
- **ALLOW TO DRY:** **Wood must be completely dry before applying CUTEK® Extreme.**
- **CLEAN YOUR EQUIPMENT:** **Clean brushes, rollers and other application equipment with mineral spirits.**

WATCH OUR VIDEO TUTORIAL

Use this step-by-step video as an additional resource to guide you through using CUTEK® Wood Reviver.

Follow the practical demonstration and expert tips to correctly restore weathered, grayed or stained wood and prepare it for protection.

Correct application and thorough rinsing help reveal the wood's natural colour and grain before applying CUTEK® Extreme.

HOW TO APPLY VIDEO • VIDÉO D'APPLICATION •

