HOW TO USE CUTEK® COLOURTONE



A SIMPLE STEP-BY-STEP GUIDE

1 CHOOSE/TEST YOUR COLOUR

Always test your chosen CUTEK® Colourtone on the actual wood before starting. Use a **CUTEK® Pre-Mixed Sample** to confirm you're happy with the final colour. Wood species, age, condition, preparation and natural grain can all affect the result.

2 PREPARE YOUR WOOD

Wood must be bare, clean and dry, with a moisture content below 17%. Prepare the surface with the appropriate CUTEK® Prepare product where required.

3 MIX THE CUTEK® COLOURTONE

Shake and knead the Colourtone tube thoroughly before opening to evenly disperse the pigment. Continue until no settled pigment remains at the bottom of the tube.

4 ADD TO CUTEK® EXTREME

Add the entire Colourtone tube to your CUTEK® Extreme clear oil, using the appropriate number of tubes for your can size. Use one 3.2 oz tube per 0.95 gal, or five tubes per 5 gal. Stir thoroughly until evenly dispersed, then stir every 15 minutes during application.

5 APPLY WITH CUTEK® EXTREME

Apply two thin coats for the initial application, **allowing the first coat to dry completely before recoating**. This generally takes 2–3 days in warm, dry conditions and longer in cool or humid weather. For routine maintenance, one coat is usually sufficient, but two may be needed if maintenance has been delayed or the wood is heavily weathered.

PRO TIP

CUTEK WOOD SOLUTIONS

After emptying the tube, **draw oil back into it.** Shake gently, then drain it into the can to remove the remaining pigment.

- NEVER APPLY CUTEK® COLOURTONE ALONE: **It must be mixed with CUTEK® Extreme clear oil.**
- TEST BEFORE STARTING: **The same Colourtone can look different across wood species and conditions.**
- MAINTAIN THE COLOUR: **Clean and recoat when the colour begins to fade.**

WATCH OUR VIDEO TUTORIAL

Use this step-by-step video as an additional resource to guide you through applying Colourtone with Extreme clear oil.

Follow the practical demonstration and expert tips to correctly mix Colourtone into Extreme and achieve an even, consistent colour.

Testing and mixing correctly from the beginning helps prevent uneven colour and delivers the best possible result.

HOW TO APPLY VIDEO • VIDÉO D'APPLICATION

