# APPLYING READY TO USE CUTEK® EXTREME

## PRE-MIXED SAMPLES




### A SIMPLE STEP-BY-STEP GUIDE

### 1 SELECT YOUR SAMPLE

Select the CUTEK® Pre-Mixed Colourtone Samples you would like to compare. Testing colours side by side will help you see how each interacts with the natural colour and grain of your wood. CUTEK® Extreme is also available as a clear sample.

### 2 PREPARE YOR WOOD

Use a clean, dry and properly prepared offcut or inconspicuous area of the actual project wood. Remove dirt, grease, coatings and surface contaminants that could affect the result.

### 3 MIX THOROUGHLY

Knead, invert and shake the sachet thoroughly to evenly disperse the Colourtone pigment through the oil. Tap the contents away from one corner, then carefully cut a small opening.

### 4 APPLY THIN COATS

Pour a small amount into a clean container or directly onto your wood sample. Using a brush, apply one thin, even coat in the direction of the grain. Use a separate clean brush or container for each colour.

### 5 ALLOW TO DRY AND COMPARE

Allow each sample to dry completely before assessing the colour. View the samples in the location and lighting where the finished wood will be seen before making your selection.

PRO TIP
CUTEK® WOOD SOLUTIONS

**Apply each sample to the same piece of wood and clearly label the colours.** This makes it much easier to compare the results under identical conditions.

- **DOUBLE-STRENGTH SAMPLE: One sample coat provides an approximate indication of two coats at standard Colourtone strength**
- **RESULTS WILL VARY: Wood species, age, condition, preparation, natural grain can all influence the final appearance.**

## WATCH OUR VIDEO TUTORIAL

**Use this step-by-step video as an additional resource to guide you through applying CUTEK® Pre-Mixed Samples.**

Follow the practical demonstration and expert tips to correctly mix, apply and compare your selected CUTEK® Colourtones on the actual wood.

Testing before purchasing helps you choose confidently and understand how the finished colour will interact with your wood's natural grain.

HOW TO APPLY VIDEO • VIDÉO D'APPLICATION

